

## Automatic Circular Saw Profilma 600 R / 600 R-XL

For Aluminium and non-ferrous heavy metal



Automatic Circular Saw Profilma 600 R with horizontal cross loader

- High-Performance automatic circular saw for aluminium and non-ferrous heavy metal
- Full automatic operation
- Direct Sawblade drive 9.2 or 18.5 KW, 400V / 50 Hz.
- R.P.M. of sawblade infinitely adjustable
- Sawblade Ø 600mm, smaller blades on request
- 3-axis control Siemens S7-300 with touch screen 5.7"
- Electronic material feed and saw blade feed by ball screw spindle and servo motor
- Cutting range max. 210 x 350 mm (height x width)

## Profilma 600 R / 600 R-XL





 Electronic material feed unit at Profilma 600R up to 1000mm feed length, at Profilma 600 R - XL up to 2000mm feed length, by ball screw spindle and servo motor

- Fivefold reversing possible
- Cut- off length from 10mm shorter cut on request
- Floating arrangement of the feeding unit
- Vertical and horizontal pneumatic clamping device – pressure pieces to be changed
- Clamping pressure reducer for all clamps with 6 manometer
- On-board profile support (option) which is connected to the feederfor good support of short profiles



Layer clamps



- Material feeder with layer clamps (Options)
- Table with changeable PVC table top Table from steel as an option



 Saw feed from back to front above the table thereby excellent removal of the swarf

 Easy change of saw blade in front of the machine

