

MG TLG 400 / 500 A

400 & 500MM SEMI AUTOMATIC RISING BLADE MITRE SAWS








PREFERRED CHOICE OF **UK** MANUFACTURERS

HIGHLY ACCURATE AND RELIABLE

FXCFI FNT SAFETY 'ECTION

WITHOUT COMPROMISING PERATIONAL **EFFECTIVENESS**





Measuring Systems & Roller Tables

IFEATURES

















Left and right mitre through 180° +/-90°

Precise control of the cutting feed rate

Enclosed cutting zone with interlocked hood

Secure horizontal and vertical pneumatic clamping

Preparation for upper zone swarf extraction

Hydropneumatic feeding of the sawblade

Blade stroke limiter for fast repetition cutting

Mist spray blade lubrication (option for pure oil mist)

Removable chip collection drawer


Moveable back fence for wide cut capacity

Option for extraction kit to extract upper and lower zones






MG TL 400 A



MG TL 500 A





SPECIFICATIONS

		TL-400 A	TL-500 A
Motor		3 HP	4 HP
Diameter		400 MM	500MM
Blade Speed		3000 RPM	3000 RPM
Diameter of Shaft		50MM	50MM
Max. Cutting Height		130MM	180MM
Height of Working Table		970MM	980MM
Dimensions		900X1000X1480MM	1200X1100X1500MM
Weight		380KG	430KG
Cutting Capacity Circular	90°	135MM	180MM
Cutting Capacity Circular	45°	115MM	150MM
Cutting Capacity Square	90°	110MM	150MM
Cutting Capacity Square	45°	100MM	120MM
Cutting Capacity Rectangle	90°	250X85MM	300X125MM
Cutting Capacity Rectangle	45°	160X70MM	145X120MM
Air Consumption		4	51

RTABLES







MG AUTOPOS MEASURING SYSTEM

- Available in 3 / 4 / 6 meter lengths
- HMI colour touchscreen
- Added option for unit with USB for office programming
- Can be configured as a material pushing system
- Memory for programming cutting lists
- Can switch from metric to imperial

ADDITRACK 3MS

- Available in 3 meter lengths.
- Roller support table with a manual set material stop and graduated scale.
- 3000mm with 280mm rollers
- Adjustable support legs are available with connection
- Optional measuring stop with metric scale
- Optional soft coated rollers to

MG TM-MEASURING **SYSTEM**

- Available in 3500 / 4500 / 6500mm lengths.
- Manual clamping of the carriage
- Switchable between metric / imperial
- Special lengths available on request
- LCD display of the cutting length (battery powered)
- Fitted with soft coated rollers to protect the material

SUPPLIER protect sensitive materials Special lengths on request MORE OPTIONS







Digital display of the cutting angle, accurate to 0.1 degree (factory fit

SOLE UK